

## TEST CERTIFICATE

No. 05320/1

Assessment to BS 5867 : 1980 Specification for Fabrics for  
Curtains and Drapes, Part 2 : Flammability Requirements using BS 5438 : 1976

### SAMPLE INFORMATION

Client Custom Covers (1984) Ltd., Quayside Road, Bitterne Manor, SOUTHAMPTON, Hampshire, SO18 1AD  
Fabric Reference CQ Advantage. Colour: Ivory.  
Dimensions 120cm by full width (145cm)  
Date Received 27.5.05  
Pre-treatment None - the material was stated to be inherently flame retardant.  
Conditioning BS 5438 : 1976, Clause 4.

### TESTING


Following the pre-treatment described above, the material was conditioned and tested according to Test 2 of BS 5438 : 1976 Method of test for flammability of vertically oriented textile fabrics and fabric assemblies subjected to a small igniting flame, using a 15 second flame application time and the results assessed according to the requirements of BS 5867 : 1980 Specification for Fabrics for Curtains and Drapes, Part 2 : Flammability Requirements. Testing was carried out on the face side of the fabric.

Specimen No.	WARP			WEFT		
	1	2	3	1	2	3
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No

It should be noted that the results may not apply to situations where there is a restricted air supply or prolonged exposure to intense heat as in a conflagration.

### CONCLUSION

The sample received meets BS 5867 : 1980 Specification for Fabrics for Curtains and Drapes, Part 2, Flammability Requirements, Type B and Clause 4.16 for Curtains and Drapes of the Guide to Fire Precautions in Existing Places of Entertainment and Like Premises (Home Office, 1994).



Mr J Leadbeater LL.B DTS  
Technical Manager  
END OF REPORT